



BRITISH STANDARD STEEL CONDUIT

TYPE TESTED BY PSB



CLASS 4 STEEL CONDUIT

MANUFACTURED TO BS 4568 PART 1 : 1970 CLASS 4
IEC 61386-21:2002

HOT DIPPED GALVANISED INSIDE AND OUTSIDE & THREAD TO BS:4568

Nominal Size (mm)	Ref. No.	Outside Diameter (mm)		Wall Thickness (mm)	No. of length per bundle	Weights (kg/m)	
		Min.	Max.			Min.	Max.
20	COT-C20-S-HDG	19.7	20.0	1.6 ± 0.15	10 x 10	0.682	0.862
25	COT-C25-S-HDG	24.6	25.0	1.6 ± 0.15	10 x 10	0.860	1.095
32	COT-C32-S-HDG	31.6	32.0	1.6 ± 0.15	5 x 10	1.133	1.432

- Threaded both ends. Option: one end fitted with coupling and the other protected by plastic end cap.
- Standard length of 3.75m without coupler.
- Material: High quality steel ensuring smooth & easy bending.

*For further information, please feel free to inquire.

HONG KONG

Many Folk Enterprises Ltd.
Flat F, 13/F, Golden Plaza,
745-747 Nathan Rd, Kln, HK
Tel: (852) 2381 4219 Fax: (852) 2397 0861
Email: manyfolk@netvigator.com
Website: www.manyfolk.com

SINGAPORE

Hipco Private Ltd.
623 Aljunied Road, #07-05B
Aljunied Industrial Complex, Singapore 389835
Tel: (65) 6745 9380 Fax: (65) 6842 3376
Email: enquiry@hipco.com.sg
Website: www.hipco.com.sg